



Floor Finishes Plan as Proposed
Scale 1:50

WINDOW SCHEDULE: GROUND FLOOR						
Win. Ref	Window Size (widthxheight)	Structural New/Existing Window	Window Location		Fire Resistance	Comments
WG 01	1475 x 450 mm	New	R 04	External	-	4 panes window, Double glazed
WG 02	770 x 450 mm	New	R 05	External	-	2 panes window, Double glazed
WG 03	1475 x 450 mm	New	R 06	External	-	4 panes window, Double glazed

● New Window
NOTE: ALL DIMENSIONS ARE APPROXIMATE.

- DO NOT SCALE FROM THIS DRAWING - USE FIGURED DIMENSIONS ONLY.
- READ IN CONJUNCTION WITH ALL OTHER CONSULTANTS / SPECIALISTS DRAWINGS, REPORT ANY DISCREPANCIES BEFORE AFFECTED WORK COMMENCES.
- ALL SETTING OUT DIMENSIONS TO BE CHECKED ON SITE BY CONTRACTOR BEFORE WORK COMMENCES.
- THIS DRAWING REMAINS COPYRIGHT OF KEPczyk PEARCE SANDERSON LTD. COPY / DISTRIBUTE ONLY WITH CONSENT OF THE AUTHOR.

Floor Finish

- New Forbo Surestep floor
Colour and finish to be confirmed
- Existing solid timber boarding to be temporary removed, and reinstated on the new limecrete slab. Make good and polish. (allow for 30% renewal to match existing)
- Existing stone paving too be temporary removed and reinstated on the new limecrete slab. Make good and use NHL3.5 mortar for rebedding.
- New Forbo Malmenium.
Colour and finish to be confirmed.
- New Porcelain tiles.
300x600mm, 10mm thk., Natural Finish
Colour and texture to be confirmed.
Manufacturer: Porcelain Tiles, Nero and Bianco Range
- New Forbo NUWAY Tufiguard anodised colour to be confirmed.
- New Porcelain tiles.
600x600mm, 10mm thk., Natural Finish
Colour and texture to be confirmed.
Manufacturer: Porcelain Tiles
- New Yorkshire pavings. Allow for reusing the existing stone paving (approx. 40sqm of existing stone paving)
- Scottish Pebbles. 30-50mm
- New resin bound gravel (SuDS) by Sureset.
Colour and finish to be confirmed.

NOTE: ARCHITECT APPROVAL REQUIRED FOR SETTING OUT THE TILES TO ENTRANCE LOBBY AREA.

NOTE: ARCHITECT APPROVAL REQUIRED FOR SETTING OUT THE FORBO MAT TO ENTRANCE LOBBY AREA.

NOTE: ARCHITECT APPROVAL REQUIRED FOR SETTING OUT THE TILES TO TOILET AREA.

'SureSet' Resin Bound Paving, 'Permeable Pathway (SUDS)', comprising 16mm surface course of SureSet aggregate (max size 6mm) hand applied and trowelled to a smooth finish, on 60mm binder course of AC 14 open surf asphalt concrete max 100/150 pen to BS EN 13108-1: 2006, laid in well compacted layers, on geotextile membrane, on 150mm well compacted granular sub base Type 3 to SHW clause 805 or 4/40, 4/20 graded crushed concrete aggregate to BS EN12620 blinded with 2/6.3mm graded concrete aggregate to BS EN12620, laid to falls and gradients indicated, on geotextile membrane, on excavated sub grade.

TENDER ISSUE

Contract Nether Alderley Parish Hall		Floor Finishes: Ground Floor Plan as Proposed	
Client Nether Alderley Parish Council	Contract No. 1905	Drawn Ash.K	Drawing No. 15
Building / Structure Nether Alderley Parish Hall	Date Jan 2020	Revision T 1	Scale 1:50 @ A1
KEPCZYK PEARCE SANDERSON ARCHITECTS, SURVEYORS & HISTORIC BUILDING CONSULTANTS		Address: 75 Wilmslow Road, Handforth, Cheshire SK9 3EN Tel: 01625 400103	